

NPS ARCHIVE
1966
MILLER, G.

AN INVESTIGATION OF THE ROUGHNESS
PARAMETER AT OCEAN STATION VESSEL VICTOR
UNDER CONDITIONS OF NEUTRAL LASPE

GERLOUS G. MILLER

2
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIF. 93940

DUDLEY KNOX LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY CA 93943-5101




GRADUATE RESEARCH REPORT

AN INVESTIGATION OF THE
ROUGHNESS PARAMETER
AT OCEAN STATION VESSEL VICTOR
UNDER CONDITIONS OF NEUTRAL LAPSE

by

Gerlous G. Miller



October 1966

NPS Archive
1966
Miller, G.

~~11/15~~
~~M5.65~~
~~(1)~~

LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIF. 93940

AN INVESTIGATION OF THE ROUGHNESS PARAMETER AT OCEAN
STATION VESSEL VICTOR UNDER CONDITIONS OF NEUTRAL LAPSE

by

GERLOUS G. MILLER

Lieutenant Commander, United States Navy

TABLE OF CONTENTS

SECTION	PAGE
1. Introduction	1
2. Selection of the Data	2
3. Derivation of the Roughness Parameter Equation	3
4. Results	5
5. Conclusions	7
6. Acknowledgements	9
7. Bibliography	10
8. Distribution List	11
9. Appendix I - Table of Surface Layer Variables	16
10. Appendix II - (Figure 1)	19

ABSTRACT

Based upon simultaneous observations of neutral-lapse conditions with the corresponding surface wind value, both for ship Victor, values of the roughness parameter have been computed. For these computations an adjunct relationship for drag coefficient after Kung (1963), is also employed, the latter relationship being primarily statistical in nature. It was found that the roughness length undergoes a variation of ten orders of magnitude as the ratio of the observed surface to geostrophic winds varies through its complete sample range from approximately 0.48 to 0.95.

LIST OF ILLUSTRATIONS

FIGURE	PAGE
1. Graph of Log \bar{z}_0 against V_{20}/V_g for Ocean Vessel Victor	

LIST OF SYMBOLS

SYMBOL	MEANING
U_*	friction velocity
H	turbulent heat flux
L	scale length (see introduction)
V	wind speed
V_{20}	wind speed at 20 meter height
V_g	surface (1000 mb) geostrophic wind speed
z	height above surface
z_0	surface roughness parameter
τ	averaged stress vector exerted at sea-air interface
C_D	geostrophic drag coefficient
ρ	air density
k	von Karman constant taken as 0.4
T	dry bulb temperature
T_s	sea surface temperature
Ro_0	surface Rossby number
f	coriolis parameter
θ	potential temperature
C_p	specific heat of air at constant pressure
g	acceleration of gravity
ESSA	Environmental Sciences Services Administration

1. Introduction.

According to the accepted theories on atmospheric turbulence, including those dealing with the Monin-Obukhov similarity principles, there exists a turbulent, atmospheric boundary layer characterized by certain near-constant parameters. These parameters are U_* , the friction-velocity, the turbulent heat-flux H , and a scale-length L defined by

$$L = - \frac{U_*^3}{k \frac{g}{\Theta} \frac{H}{c_p \rho}} \quad (1)$$

In the present study, where case selection was restricted to neutral-lapse cases at Ship Victor, L is infinite ($H=0$) and the usual logarithmic profile

$$V = \frac{U_*}{k} \ln \frac{z}{z_0}, \quad k = 0.4 \quad (2)$$

has been assumed to be valid. Here V is the wind speed at the anemometer-level, which was taken as $z = 2000$ cm (after some correspondence with cognizant U.S. Coast Guard Officials). No attempt was made to introduce a second statistical degree of freedom, in the form of the datum-level displacement, mainly because accurate wave-heights were not included in the coded data cards for any of the available periods under study.

As is well-known, most operating numerical prediction centers, for example, that of the National Meteorological Center in Suitland, Maryland, make use of average values of the geostrophic drag coefficient, C_D , obtainable from

$$\tau = C_D^2 V_g^2 = \rho U_*^2 \quad (3)$$

The right side of (3) is dependent upon the roughness parameter z_0 (see equation (4) below), grossly averaged, and then taken to be representative of NMC grid points. Operationally, there seems to be little cure for injecting daily deviations of C_D from its seasonal average, but this study was undertaken to investigate the possibility of the existence of such deviations.

2. Selection of the Data.

All data were taken from punched data cards provided by the National Weather Records Center at Asheville, North Carolina. The data cards employed spanned the period 1959 - 1960 at Ocean Station Vessel "Victor" employing only the section 116 (Marine Surface Observations) part of the coded data. Since only 6 to 10 meters of elevation is involved between sea and instrument levels, a neutral lapse would be "isothermal" over this vertical span. However, since both the sea and dry bulb temperatures have, with very few exceptions, been preliminarily rounded off to the nearest degree, the selection criterion for "neutral" was relaxed to the following:

$$T - T_s = \pm 1^\circ F$$

Each of the neutral cases were carefully cited as to date and time, and if the observation time coincided with that of a 00 GCT sea-level analysis in the file of Northern Hemisphere Synoptic Weather Maps covering the same period (1959 - 1960), the particular neutral case was accepted for further computation.

For each case accepted, the shipboard wind speed in knots was recorded from the card file. For the same case the geostrophic wind was carefully read off by measuring the perpendicular spacing between 5 mb

isobars on the synoptically-timed sea-level chart. These measurements were made using dividers; then appropriate distance measurements were converted into a geostrophic wind at the latitude of "Victor" (34°N, 164°E). It was found that use of the geostrophic wind scale on the individual weather maps yielded objectively sound values provided cases where (1) fronts occurred close to Victor, or (2) the isobars in the vicinity of Victor were strongly-curved cyclonically, were rejected.

3. Derivation of the roughness-parameter equation.

First consideration was given to the neutral wind profile applicable at 20 meters:

$$V_{20} = \frac{U_*}{k} \ln\left(\frac{2000}{z_0}\right) \quad (4)$$

with $U_* = \sqrt{\frac{\tau}{\rho}}$ considered constant in the surface layer. Kung (1963) defines U_* of equation (4) in accordance with

$$U_* = C_D V_g \quad (5)$$

where C_D is his drag coefficient, but is to be interpreted as the square root of that of Cressman (1960). Furthermore, Kung's statistical analysis of U_* resulting from (4) has led to the following empirical result for C_D :

$$C_D = \frac{0.205}{\log R_{00} - 0.556} \quad , \quad R_{00} = \frac{V_g}{f z_0} \quad (6)$$

It should be noted that R_{00} as defined in equation (6) is a dimensionless parameter describing the large-scale frictional aspects of the boundary layer, and has been called the surface Rossby number.

Combination of equations (4, 5) leads to the result:

$$C_D = \frac{k \left(\frac{V_{20}}{V_g} \right)}{\ln \left(\frac{2000}{z_0} \right)} = \frac{k \frac{V_{20}}{V_g}}{2.3026 \log \left(\frac{2000}{z_0} \right)} \quad (7)$$

This result, combined with equation (6) yields

$$\frac{0.205}{\log V_g - \log z_0 - \log f - 0.556} = \frac{k \frac{V_{20}}{V_g}}{(2.3026) [\log 2000 - \log z_0]} \quad (8)$$

It should be noted that (8) is valid only for the statistical range of Kung's result (6) and for those conditions under which a neutral boundary layer may be considered to apply. Within these rather broad limitations, the solution for $\log z_0$ is

$$\log z_0 = \log V_g - \log f - 0.556 - \frac{0.205(2.3026)}{\left(\frac{V_{20}}{V_g} \right)} (\log 2000 - \log z_0) \quad (9)$$

or more specifically, with $k = 0.4$, $\log 2000 = 3.30103$ and $\log f = -4.0886$, equation (9) becomes

$$\log z_0 = \log V_g + 3.5326 - \frac{(\log V_g + 0.2316)}{(1 - 0.8474 \frac{V_{20}}{V_g})} \quad (10)$$

Introduce the notation

$$X = \frac{1}{(1 - 0.8474 \frac{V_{20}}{V_g})} \quad (11)$$

and the resulting expression for $\log z_0$ finally becomes

$$\log z_0 = \log V_g + 3.5326 - (\log V_g + 0.2316) X \quad (12)$$

Since it is customary to solve for z_0 in cm, and f has been expressed in sec^{-1} , all wind speeds V_{20} , V_g have been converted from kts to cm sec^{-1} using the conversion factor

$$1 \text{ knot} = 51.479 \text{ cm sec}^{-1}$$

Equation (12) is the working relationship for the calculations made in this study.

4. Results.

All pertinent boundary layer parameters have listed in Table 1. (see Appendix) for each of the 55 cases which fitted the acceptance criteria. It is noted that V_{20}/V_g varied from a minimum of 0.489 on 1 January, 1959 to a maximum of 0.969 on 25 November 1959. Moreover, V_{20}/V_g appears as a linear variable within the denominator of X . It is therefore evident that the single factor which most strongly affects the value of $\log \bar{z}_0$ is X , which varies from a minimum of 1.708 to a maximum of 5.596, corresponding respectively to the two wind ratios just cited. On the other hand, the contribution of the only other variable in equation (12), $\log V_g$, was relatively minimal varying only by a multiplicative of factor of 0.90 to 1.10 relative to the sample-mean of $\log V_g$.

Thus each value of $\log \bar{z}_0$ was coupled with the simultaneous ratio of X , defined by equation (11). As the above comments suggest, there was an extremely regular tendency for $\log \bar{z}_0$ to decrease with increasing (V_{20}/V_g) . This was true both in the 55 individual computations, as well as in class-grouped averages of both $\log \bar{z}_0$ and V_{20}/V_g . The grouping was based on classes of V_{20}/V_g according to the values of these wind ratios in the number ranges 0.45-0.50, 0.50-0.55,....., 0.85-0.90, 0.90-0.95. The corresponding class-mean averages of $\log \bar{z}_0$ were then computed for each wind-ratio class. The paired class-average values were as follows:

V_{20}/V_g	0.45-0.50 0.4893	0.50-0.55 0.5130	0.55-0.60 0.5638	0.60-0.65 0.6323	0.65-0.70 0.6772	0.70-0.75 0.7261
$(\log \bar{z}_0)$ Average	+0.7406	+0.4500	+0.1986	-0.8296	-1.3031	-2.2320

V_{20}/V_g	0.75-0.80 0.7651	0.80-0.85 0.8203	0.85-0.90 0.8624	0.90-0.95 0.9151
(log \bar{Z}_0) Average	-3.4514	-4.5050	-5.7238	-8.6549

The results by class-groups so closely reflected the individual pairings that the final results have been graphed in Figure 1, solely by paired class-averages. The resulting graph essentially presents log \bar{Z}_0 in the functional form

$$\log \bar{Z}_0 = (\overline{\log V_g} + 3.5326) - [\overline{\log V_g} + 0.2316] (1 - 0.8474 \frac{V_{20}}{V_g})^{-1} \quad (13)$$

where $\overline{\log V_g}$ is the sample-mean of the individual values of log V_g . In other words, log \bar{Z}_0 has a general simplified form

$$\log \bar{Z}_0 = C_1 - C_2 (1 - 0.8474 \frac{V_{20}}{V_g})^{-1} \quad (14)$$

where C_1 is the constant within the first parentheses of (13) and C_2 , that within the bracket of equation (13).

Figure 1 shows that log \bar{Z}_0 tends to decrease towards $-\infty$ as V_{20} approaches V_g whereas at the other extreme for $V_{20}/V_g = 0.489$, $\bar{Z}_0 = 5.5$ cm, an unusually high value for an oceanic area. Upon exclusion of that class-group V_{20}/V_g with values in the range 0.95 to 1.00 (these were considered unrealistically large for the neutral, steady state case), the mean-value of \bar{Z}_0 turned out to be intermediate between the extreme oceanic roughness-values $\bar{Z}_0 = 0.1$ cm (for $V_g \geq 10$ kts) and $\bar{Z}_0 = 0.01$, for $V_g < 10$ kts, employed by the General Circulation Laboratory of ESSA. Their approach, also empirical, evidently presumes that stronger surface winds and a consequent greater roughness parameter, ensues from the

assumption of a greater geostrophic wind. Such a modeling assumption need not be inconsistent with the results found here, but merely an expression of the relative scopes from which the turbulence problem has been viewed. Some further physical justification of equation (14) is offered in Section 5.

5. Conclusions

It has already been shown in the preceding section that the application of neutral boundary layer wind data chosen purely at random leads to a tenfold variation in $\text{Log } Z_0$. However, recent theories of the planetary boundary-layer, specifically those of H.H. Lettau (1961) and Blackadar (1962) for the barotropically neutral atmosphere, but with variable exchange coefficient $K=K(\bar{z})$ led to spiral-type solutions with increasing \bar{z} . One of the main shortcomings of these theories in ascribing proper values of the surface-stress is the assumption of zero acceleration in the large scale wind field. Kung (1963) has given average values of V_{16}/V_g at numerous geographic locations over the oceans, these based upon rather long-averaging periods. When one averages over his summer and winter climatological ratios, the resultant V_{16}/V_g reflects both near-neutral and quasi-steady state conditions. This average value of V_{16}/V_g was 0.68, and extrapolation gives $V_{20}/V_g = 0.70$.

In this study, our median class centered about 0.70, but large deviations in V_{20}/V_g relative to 0.7 did occur, with higher wind ratios reflecting supposedly a smoother air-ocean interface. The interpretation of this surprising result must lie in the use of individual data applied to steady-state theory, which represents improper application of limited theory.

The defects seem to occur in the areas of

- (1) the non-inclusion of acceleration terms in the boundary-layer theory.
- (2) the slow variation rate of a given sea state, even though the impressed large-scale geostrophic wind undergoes significant change.

Both areas (1) and (2) are interrelated through the basic unknown, the large-scale acceleration, and its feedback rate to the interface. For example, consider our $V_{20}/V_g = 0.5$ relative to steady-state turbulence theories. This was taken to mean that V_g (at gradient level) had responded to an acceleration to which the surface wind was unable to respond, except at much greater lag time. Hence in entering equation (12), X is below average and the resulting $\log Z_0$ greater than average. On the other hand, an individual case wherein $V_{20}/V_g = 0.90$ compared to the steady-state value of 0.7 indicates that overhead a decrease in V_g had already taken place without a corresponding decrease in V_{20} , due largely to the greater lag-response time at the surface.

The main conclusion of this study is not that of questioning the validity of values of Z_0 in operational use. Rather, its purpose is to point to areas where the turbulence theory seems to be in need of improvement, especially with regard to the inclusion of unsteady-state conditions in the free-atmosphere, and the difference in response-time in the boundary layer as the interface is approached. The lag time consideration is especially compounded when there is an oceanic interface subject to storm-wave disturbances of short wavelength.

6. Acknowledgements

The original idea for this paper was that of Professor Frank L. Martin of the United States Naval Postgraduate School. His invaluable advice and encouragement are gratefully acknowledged.

BIBLIOGRAPHY

1. Blackadar, A.K., The Vertical Distribution of Wind and Turbulent Exchange in a Neutral Atmosphere., Journal of Geophysical Research, Vol. 67, No. 8, pp. 3095-3102, July, 1962
2. Cressman, G.P, Improved Terrain Effects in Barotropic Forecasts, Monthly Weather Review, 88, pp. 327-342, 1960.
3. Kung, E.C., Climatology of Aerodynamic Roughness Parameter and Energy Dissipation in the Planetary Boundary Layer over the Northern Hemisphere, University of Wisconsin, Department of Meteorology, Annual Report 1963. Studies of the Effects of Variations in Boundary Conditions on the Atmospheric Boundary Layer, pp. 37-96, November, 1963. (Edited by H.H. Lettau).
4. Lettau, H.H., Wind Profile, Surface Stress and Geostrophic Drag Coefficients in the Atmospheric Surface Layer, Advances in Geophysics, Vol. 6, pp. 241-257, 1959.
5. Lettau, H.H., Theoretical Wind Spirals in the Boundary Layer of a Barotropic Atmosphere, pp. 143-170 of Annual Report, contract DA-36-039-SC-80282 (USEPG, Fort Huachuca, Arizona) University of Wisconsin, 1961.
6. Lumley, J.L. and H.A. Panofsky, The Structure of Atmospheric Turbulence Monographs and Texts in Physics and Astronomy, Vol. 12, 1964.
7. Manier, G. and F. Moller, Determination of Heat Balance at the Boundary Layer over the Sea., Meteorologisch-Geophysikalisches Institut, Johannes Gutenberg - Universitat Mainz, Germany. Final Report, contract No. AF61(052)-315, December, 1961.
8. Martin, F.L., A Theory for the Derivation of the 10-Meter Wind, Unpublished Paper, 1966.
9. Riley, L.M., The Determination of Richardson Number and Roughness Parameter at Ocean Vessel "Victor", Thesis, 1965.
10. Reference Manual 116, U.S. Marine Surface Observations 1949-1961, rev. September 1964.

DISTRIBUTION LIST

	Addressee	No. of Copies
1.	Author: LCDR Gerlous Miller Fleet Weather Facility Norfolk, Virginia	3
2.	Advisor: Prof. F.L. Martin U.S. Naval Postgraduate School Monterey, California	2
3.	Library U.S. Naval Postgraduate School Monterey, California 93940	2
4.	Dept. of Meteorology & Oceanography U.S. Naval Postgraduate School Monterey, California 93940	1
5.	Defense Documentation Center Cameron Station Alexandria, Virginia 22314	20
6.	Office of the U.S. Naval Weather Service U.S. Naval Station(Washington Navy Yard Annex) Washington, D.C. 20390	1
7.	Officer in Charge Naval Weather Research Facility U.S. Naval Air Station, Bldg. R-48 Norfolk, Virginia 23511	1
8.	Commanding Officer and Director Navy Electronics Laboratory Attn: Code 2230 San Diego, California 92152	1
9.	Officer in Charge Fleet Numerical Weather Facility U.S. Naval Postgraduate School Monterey, California 93940	1
10.	Director, Naval Research Laboratory Attn: Tech. Services Info. Officer Washington, D.C. 20390	1
11.	Program Director for Meteorology National Science Foundation Washington, D.C.	1

12. American Meteorological Society
45 Beacon Street
Boston, Massachusetts 1
13. Commander, Air Weather Service
Military Airlift Command
U.S. Air Force
Scott Air Force Base, Illinois 62226 2
14. U.S. Department of Commerce
Weather Bureau
Washington, D.C. 2
15. Office of Naval Research
Department of the Navy
Washington, D.C. 20360 1
16. U.S. Naval Oceanographic Office
Washington, D.C. 20390 1
17. Program Director for Oceanography
National Science Foundation
Washington, D.C. 1
18. Director
National Oceanographic Data Center
Washington, D.C. 1
19. Director
Woods Hole Oceanographic Institution
Woods Hole, Massachusetts 02543 1
20. ~~Chairman~~
Department of Meteorology and Oceanography
New York University
University Heights, Bronx
New York, New York 1
21. Department of Meteorology
University of California
Los Angeles, California 1
22. Department of the Geophysical Sciences
University of Chicago
Chicago, Illinois 1
23. Department of Atmospheric Science
Colorado State University
Fort Collins, Colorado 1
24. Department of Engineering Mechanics
University of Michigan
Ann Arbor, Michigan 1

25. Department of Meteorology
University of Utah
Salt Lake City, Utah 1
26. National Center for Atmospheric Research
Boulder, Colorado 1
27. Department of Meteorology and Climatology
University of Washington
Seattle, Washington 98105 1
28. Department of Meteorology
University of Wisconsin
Madison, Wisconsin 1
29. Department of Meteorology
Florida State University
Tallahassee, Florida 1
30. Department of Meteorology
Massachusetts Institute of Technology
Cambridge, Massachusetts, 03139 1
31. Department of Meteorology
Pennsylvania State University
University Park, Pennsylvania 1
32. Hawaii Institute of Geophysics
University of Hawaii
Honolulu, Hawaii 1
33. University of Oklahoma
Research Institute
Norman, Oklahoma 1
34. Atmospheric Science Branch
Science Research Institute
Oregon State College
Corvallis, Oregon 1
35. The University of Texas
Electrical Engineering Research Laboratory
University Station
Austin, Texas 78712 1
36. Department of Meteorology
Texas A&M University
College Station, Texas 77843 1
37. Lamont Geological Observatory
Columbia University
Palisades, New York 1
38. Division of Engineering and Applied Physics
Room 206, Pierce Hall
Harvard University
Cambridge, Massachusetts 1

- | | | |
|-----|--|---|
| 39. | Department of Mechanics
The John Hopkins University
Baltimore, Maryland | 1 |
| 40. | University of California
E.O. Lawrence Radiation Laboratory
Livermore, California | 1 |
| 41. | Department of Astrophysics and Atmospheric Physics
University of Colorado
Boulder, Colorado | 1 |
| 42. | The Travelers Research Center, Inc.
650 Main Street
Hartford, Connecticut | 1 |
| 43. | Department of Meteorology
University of Melbourne
Grattan Street
Parkville, Victoria, Australia | 1 |
| 44. | Bureau of Meteorology
Department of the Interior
Victoria and Drummond Streets
Carlton, Victoria, Australia | 1 |
| 45. | International Antarctic Analysis Centre
468 Londala Street
Melbourne, Victoria, Australia | 1 |
| 46. | C.S.I.R.O.
Division of Meteorological Physics
Station Street
Aspendale, Victoria, Australia | 1 |
| 47. | Institut f. Meteor. u.
Geophysik Universitat Innsbruck
Schopfstrasse 41, Innsbruck, Austria | 1 |
| 48. | Department of Meteorology
McGill University
Montreal, Canada | 1 |
| 49. | Central Analysis Office
Meteorological Branch
Regional Adm. Building
Inter. Airport
Dorval, Quebec, Canada | 1 |
| 50. | Meteorological Office
315 Bloor Street West
Toronto 5, Ontario, Canada | 1 |

- | | | |
|-----|--|---|
| 51. | Institut fur Theoretische Meteorologie
Frsie Universitat Berlin
Berlin-Dahlem
Thiel-alien 49
Federal Republic of Germany | 1 |
| 52. | Department of Meteorology
The Hebrew University
Jerusalem, Isreal | 1 |
| 53. | Geophysical Institute
Tokyo University
Tokyo, Japan | 1 |
| 54. | Department of Meteorology
Instituto de Geofisica
Universidad Nacional de Mexico
Mexico 20, D.F. Mexico | 1 |
| 55. | New Zealand Meteorological Service
P.O. Box 722
Wellington, G.E. New Zealand | 1 |
| 56. | Institute of Geophysics
University of Bergen
Bergen, Norway | 1 |
| 57. | Department of Meteorology
Imperial College of Science
South Kensington
London S.W. 7, United Kingdom | 1 |
| 58. | Director
Pacific Oceanographic Group
Nanaimo, British Columbia
Canada | 1 |

APPENDIX I - TABLE 1

Table of Variables Needed In Solving
For Log Z_0 , Listed by Case and Date

TABLE 1

Date	$T_s(^{\circ}\text{F})$	$T(^{\circ}\text{F})$	$V_g(\text{kts})$	V_{20} (kts)	$\text{Log } V_g$	V_{20}/V_g	X	$\text{Log } \bar{z}_0$
1/2/59	63	64	55	30	3.452	0.545	1.859	+0.135
1/3/59	67	67	50	38	3.401	0.760	2.372	-2.991
1/15/59	61	60	50	31	3.401	0.620	2.107	-0.720
1/19/59	61	61	23	16	3.073	0.696	2.437	-1.449
1/23/59	60	61	47	23	3.384	0.489	1.708	+0.741
1/25/59	60	61	25	22	3.110	0.880	3.937	-6.512
1/26/59	60	60	50	39	3.401	0.780	2.950	-3.784
1/30/59	58	58	28	18	3.159	0.643	2.198	-0.762
2/2/59	59	58	22	20	3.054	0.909	4.355	-7.724
2/3/59	59	60	41	23	3.325	0.561	1.906	+0.080
2/8/59	62	62	29	28	3.174	0.965	5.492	-11.996
2/10/59	61	60	23	22	3.073	0.957	5.288	-10.872
2/15/59	63	63	22	19	3.054	0.863	2.831	-2.714
2/17/59	63	63	14	12	2.858	0.857	3.654	-4.897
2/18/59	64	65	31	20	3.203	0.645	2.207	-0.845
3/3/59	63	63	43	39	3.345	0.907	4.322	-8.579
3/14/59	64	63	30	26	3.189	0.867	2.854	-3.040
3/19/59	63	62	55	50	3.452	0.909	4.357	-9.066
3/23/59	62	61	27	24	3.143	0.889	4.057	-7.015
3/31/59	63	63	22	16	3.054	0.727	2.606	-1.977
4/4/59	59	59	32	22	3.217	0.688	2.398	-1.518
4/5/59	61	61	29	16	3.174	0.552	1.879	+0.309
4/9/59	63	63	23	13	3.073	0.565	1.919	+0.265
4/10/59	64	64	20	11	3.013	0.550	1.871	+0.474
4/11/59	64	64	25	23	3.110	0.920	4.537	-8.518
4/14/59	63	64	26	21	3.127	0.808	3.171	-3.988
4/17/59	63	63	31	30	3.203	0.967	5.549	-12.324
4/18/59	63	63	31	21	3.203	0.677	2.347	-1.325
10/9/59	74	74	29	23	3.174	0.793	3.049	-3.677
10/18/59	72	71	31	27	3.203	0.871	3.817	-6.374
10/20/59	72	73	38	25	3.291	0.658	2.260	-1.140
10/28/59	65	64	38	21	3.291	0.553	1.881	+0.197
10/29/58	69	68	31	27	3.203	0.871	3.817	-6.374
10/30/59	69	68	29	25	3.174	0.862	3.711	-5.931
11/7/59	65	65	27	18	3.143	0.667	2.299	-1.084
11/11/59	71	71	24	23	3.082	0.958	5.311	-10.983
11/17/59	71	71	40	32	3.314	0.800	3.104	-4.157
11/22/59	67	66	29	28	3.174	0.965	5.492	-11.996
11/25/59	69	69	31	30	3.203	0.969	5.596	-12.484
11/27/59	70	70	26	24	3.127	0.924	4.604	-8.802
12/14/59	68	67	17	10	2.942	0.589	1.995	+0.143
12/15/59	68	68	27	22	3.143	0.815	3.233	-4.231
12/16/59	68	69	34	22	3.243	0.647	2.215	-0.922
12/17/59	68	68	33	26	3.220	0.788	3.006	-3.622
12/18/59	69	69	38	33	3.291	0.869	3.789	-6.526
12/20/59	69	69	37	31	3.280	0.838	3.448	-5.296

TABLE 1
(Continued)

Date	T _s (°F)	T (°F)	V _g (kts)	V ₂₀ (kts)	Log V _g	V ₂₀ /V _g	X	Log Z ₀
1/1/60	67	66	38	35	3.291	0.921	4.560	-9.241
1/6/60	66	66	34	30	3.243	0.882	3.964	-6.996
1/7/60	66	65	27	26	3.143	0.963	5.426	-11.635
1/11/60	65	64	32	28	3.217	0.875	3.867	-6.585
1/17/60	66	66	42	30	3.335	0.714	2.533	-2.166
1/28/60	64	63	39	25	3.303	0.641	2.189	-0.900
2/10/60	64	64	24	18	3.082	0.750	2.744	-2.479
2/19/60	64	64	22	21	3.054	0.954	5.222	-10.571
2/22/60	63	64	38	32	3.291	0.737	2.662	-2.553

APPENDIX II

Figure 1 Graph of $\log Z_0$ Against V_{20}/V_g for Ocean Vessel Victor




Fig.1 Graph of $\text{Log } z_0$ against V_{20}/V_g for Ocean Vessel Victor

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
NAVAL POSTGRADUATE SCHOOL		UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE			
AN INVESTIGATION OF THE ROUGHNESS PARAMETER AT OCEAN STATION VESSEL VICTOR UNDER CONDITIONS OF NEUTRAL LAPSE			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
GRADUATE RESEARCH REPORT			
5. AUTHOR(S) (Last name, first name, initial)			
MILLER, GERLOUS G. Lieutenant Commander, U. S. Navy			
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS	
13 October 1966	27	10	
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)		
b. PROJECT NO.			
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)		
d.			
10. AVAILABILITY/LIMITATION NOTICES			
Qualified requesters may obtain copies of this report from DDC.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		Chief of Naval Operations (OP-09B7) Navy Department Washington, D. C. 20350	
13. ABSTRACT			
<p>Based upon simultaneous observations of neutral-lapse conditions with the corresponding surface wind value, both for ship Victor, values of the roughness parameter have been computed. For these computations an adjunct relationship for drag coefficient after Kung (1963) is also employed, the latter relationship being primarily statistical in nature. It was found that the roughness length undergoes a variation of ten orders of magnitude as the ratio of the observed surface to geostrophic winds varies through its complete sample range from approximately 0.48 to 0.95.</p>			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
ROUGHNESS PARAMETER						
OCEAN VESSEL VICTOR						
NEUTRAL LAPSE						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

~~SECRET~~

thesM5865

An investigation of the roughness parame



3 2768 001 88381 2

DUDLEY KNOX LIBRARY